

Shredder-Grinder DZ 750 E



Applications

The multi-purpose shredders of the DOPPSTADT DZ series process old growth, root wood, green waste, bulky stem wood and much more. The combination of a slow-going, contaminant-resistant pre-shredding system and a downstream high-speed post-processing system makes for the perfect solution for the most demanding shredding tasks.

Advantages

- Shredding and grinding in one machine
- Production of finished goods in one machine
- Easy one-man operation
- Contaminant-resistant high-speed shredding
- Application of very strong magnets

Dimensions

Chassis	Semi-trailer
Total weight (kg)	46000
Length (mm)	18516
Width (mm)	2550
Height (mm)	4100
Transport width (mm)	2550
Transport height (mm)	3980
Transport length (mm)	13550

Drive

Engine type electrical

Make Three-phase motor

Motor power (kW / PS) 450 / Rollerspeed 25/21

Discharge conveyor

Width (mm) 1500 Length (mm) 7000

Flail drum

 Width (mm)
 1750

 Diameter (mm)
 1100

 Speed (min-1)
 1080

 Number of Flail teeth
 36

Roller

Number of rollers1Roller Length (mm)3000Roller Diameter (mm)600Roller Speed (min-1)25/21Number of roller teeth21/42Loading height (mm)3000



